
Kademlia Documentation

Release 2.2.1

Brian Muller

May 03, 2020

CONTENTS

1 Installation 3

2 Usage 5

3 Running Tests 7

4 Fidelity to Original Paper 9

5 Querying the DHT 11

6 Kademlia API 13

6.1 kademlia package 13

6.1.1 kademlia.crawling module 13

6.1.2 kademlia.network module 14

6.1.3 kademlia.node module 14

6.1.4 kademlia.protocol module 15

6.1.5 kademlia.routing module 15

6.1.6 kademlia.storage module 16

6.1.7 kademlia.utils module 17

7 Indices and tables 19

Python Module Index 21

Index 23

Note: This library assumes you have a working familiarity with [asyncio](#).

This library is an asynchronous Python implementation of the [Kademlia distributed hash table](#). It uses [asyncio](#) to provide asynchronous communication. The nodes communicate using [RPC over UDP](#) to communicate, meaning that it is capable of working behind a [NAT](#).

This library aims to be as close to a reference implementation of the [Kademlia paper](#) as possible.

INSTALLATION

The easiest (and best) way to install kademia is through `pip`:

```
$ pip install kademia
```


USAGE

To start a new network, create the first node. Future nodes will connect to this first node (and any other nodes you know about) to create the network.

```
import logging
import asyncio

from kademia.network import Server

handler = logging.StreamHandler()
formatter = logging.Formatter('%(asctime)s - %(name)s - %(levelname)s - %(message)s')
handler.setFormatter(formatter)
log = logging.getLogger('kademia')
log.addHandler(handler)
log.setLevel(logging.DEBUG)

loop = asyncio.get_event_loop()
loop.set_debug(True)

server = Server()
loop.run_until_complete(server.listen(8468))

try:
    loop.run_forever()
except KeyboardInterrupt:
    pass
finally:
    server.stop()
    loop.close()
```

Here's an example of bootstrapping a new node against a known node and then setting a value:

```
import logging
import asyncio
import sys

from kademia.network import Server

if len(sys.argv) != 5:
    print("Usage: python set.py <bootstrap node> <bootstrap port> <key> <value>")
    sys.exit(1)

handler = logging.StreamHandler()
formatter = logging.Formatter('%(asctime)s - %(name)s - %(levelname)s - %(message)s')
```

(continues on next page)

(continued from previous page)

```
handler.setFormatter(formatter)
log = logging.getLogger('kademlia')
log.addHandler(handler)
log.setLevel(logging.DEBUG)

async def run():
    server = Server()
    await server.listen(8469)
    bootstrap_node = (sys.argv[1], int(sys.argv[2]))
    await server.bootstrap([bootstrap_node])
    await server.set(sys.argv[3], sys.argv[4])
    server.stop()

asyncio.run(run())
```

Note: You must have at least two nodes running to store values. If a node tries to store a value and there are no other nodes to provide redundancy, then it is an exception state.

RUNNING TESTS

To run tests:

```
$ pip install -r dev-requirements.txt  
$ pytest
```


FIDELITY TO ORIGINAL PAPER

The current implementation should be an accurate implementation of all aspects of the paper except one - in Section 2.3 there is the requirement that the original publisher of a key/value republish it every 24 hours. This library does not do this (though you can easily do this manually).

QUERYING THE DHT

If you just want to query the network, you can use the example query script. For instance:

```
$ python examples/get.py 1.2.3.4 8468 SpecialKey
```

The query script is simple:

```
import logging
import asyncio
import sys

from kademia.network import Server

if len(sys.argv) != 4:
    print("Usage: python get.py <bootstrap node> <bootstrap port> <key>")
    sys.exit(1)

handler = logging.StreamHandler()
formatter = logging.Formatter('%(asctime)s - %(name)s - %(levelname)s - %(message)s')
handler.setFormatter(formatter)
log = logging.getLogger('kademia')
log.addHandler(handler)
log.setLevel(logging.DEBUG)

async def run():
    server = Server()
    await server.listen(8469)
    bootstrap_node = (sys.argv[1], int(sys.argv[2]))
    await server.bootstrap([bootstrap_node])

    result = await server.get(sys.argv[3])
    print("Get result:", result)
    server.stop()

asyncio.run(run())
```

Check out the examples folder for other examples.

KADEMLIA API

Kademlia is a Python implementation of the Kademlia protocol which utilizes the asyncio library.
The best place to start is the examples folder before diving into the API.

6.1 kademlia package

The best place to start is the examples folder before diving into the API.

6.1.1 kademlia.crawling module

class `kademlia.crawling.NodeSpiderCrawl` (*protocol, node, peers, ksize, alpha*)

Bases: `kademlia.crawling.SpiderCrawl`

Create a new C{SpiderCrawl}er.

Parameters

- **protocol** – A `KademliaProtocol` instance.
- **node** – A `Node` representing the key we're looking for
- **peers** – A list of `Node` instances that provide the entry point for the network
- **ksize** – The value for k based on the paper
- **alpha** – The value for alpha based on the paper

async find()

Find the closest nodes.

class `kademlia.crawling.RPCFindResponse` (*response*)

Bases: `object`

A wrapper for the result of a RPC find.

Parameters **response** – This will be a tuple of (<response received>, <value>) where <value> will be a list of tuples if not found or a dictionary of {'value': v} where v is the value desired

get_node_list()

Get the node list in the response. If there's no value, this should be set.

get_value()

happened()

Did the other host actually respond?

has_value()

class `kademlia.crawling.SpiderCrawl` (*protocol, node, peers, ksize, alpha*)

Bases: `object`

Crawl the network and look for given 160-bit keys.

Create a new `C{SpiderCrawl}`er.

Parameters

- **protocol** – A `KademliaProtocol` instance.
- **node** – A `Node` representing the key we're looking for
- **peers** – A list of `Node` instances that provide the entry point for the network
- **ksize** – The value for `k` based on the paper
- **alpha** – The value for `alpha` based on the paper

class `kademlia.crawling.ValueSpiderCrawl` (*protocol, node, peers, ksize, alpha*)

Bases: `kademlia.crawling.SpiderCrawl`

Create a new `C{SpiderCrawl}`er.

Parameters

- **protocol** – A `KademliaProtocol` instance.
- **node** – A `Node` representing the key we're looking for
- **peers** – A list of `Node` instances that provide the entry point for the network
- **ksize** – The value for `k` based on the paper
- **alpha** – The value for `alpha` based on the paper

async find()

Find either the closest nodes or the value requested.

6.1.2 kademlia.network module

6.1.3 kademlia.node module

class `kademlia.node.Node` (*node_id, ip=None, port=None*)

Bases: `object`

Simple object to encapsulate the concept of a Node (minimally an ID, but also possibly an IP and port if this represents a node on the network). This class should generally not be instantiated directly, as it is a low level construct mostly used by the router.

Create a Node instance.

Parameters

- **node_id** (*int*) – A value between 0 and 2^{160}
- **ip** (*string*) – Optional IP address where this Node lives
- **port** (*int*) – Optional port for this Node (set when IP is set)

distance_to (*node*)

Get the distance between this node and another.

same_home_as (*node*)

```
class kademlia.node.NodeHeap (node, maxsize)
    Bases: object

    A heap of nodes ordered by distance to a given node.

    Constructor.

    @param node: The node to measure all distnaces from. @param maxsize: The maximum size that this heap
    can grow to.

    get_ids ()

    get_node (node_id)

    get_uncontacted ()

    have_contacted_all ()

    mark_contacted (node)

    popleft ()

    push (nodes)
        Push nodes onto heap.

        @param nodes: This can be a single item or a C{list}.

    remove (peers)
        Remove a list of peer ids from this heap. Note that while this heap retains a constant visible size (based
        on the iterator), it's actual size may be quite a bit larger than what's exposed. Therefore, removal of nodes
        may not change the visible size as previously added nodes suddenly become visible.
```

6.1.4 kademlia.protocol module

6.1.5 kademlia.routing module

```
class kademlia.routing.KBucket (rangeLower, rangeUpper, ksize, replacementNodeFactor=5)
    Bases: object

    add_node (node)
        Add a C{Node} to the C{KBucket}. Return True if successful, False if the bucket is full.

        If the bucket is full, keep track of node in a replacement list, per section 4.1 of the paper.

    depth ()

    get_nodes ()

    has_in_range (node)

    head ()

    is_new_node (node)

    remove_node (node)

    split ()

    touch_last_updated ()

class kademlia.routing.RoutingTable (protocol, ksize, node)
    Bases: object

    @param node: The node that represents this server. It won't be added to the routing table, but will be needed
    later to determine which buckets to split or not.
```

add_contact (*node*)

find_neighbors (*node*, *k=None*, *exclude=None*)

flush ()

get_bucket_for (*node*)

Get the index of the bucket that the given node would fall into.

is_new_node (*node*)

lonely_buckets ()

Get all of the buckets that haven't been updated in over an hour.

remove_contact (*node*)

split_bucket (*index*)

class `kademlia.routing.TableTraverser` (*table*, *startNode*)

Bases: `object`

6.1.6 kademlia.storage module

class `kademlia.storage.ForgetfulStorage` (*ttl=604800*)

Bases: `kademlia.storage.IStorage`

By default, max age is a week.

__getitem__ (*key*)

Get the given key. If item doesn't exist, raises `C{KeyError}`

__setitem__ (*key*, *value*)

Set a key to the given value.

cull ()

get (*key*, *default=None*)

Get given key. If not found, return default.

iter_older_than (*seconds_old*)

Return the an iterator over (key, value) tuples for items older than the given secondsOld.

class `kademlia.storage.IStorage`

Bases: `abc.ABC`

Local storage for this node. IStorage implementations of get must return the same type as put in by set

abstract **__getitem__** (*key*)

Get the given key. If item doesn't exist, raises `C{KeyError}`

abstract **__setitem__** (*key*, *value*)

Set a key to the given value.

abstract **get** (*key*, *default=None*)

Get given key. If not found, return default.

abstract **iter_older_than** (*seconds_old*)

Return the an iterator over (key, value) tuples for items older than the given secondsOld.

6.1.7 kademlia.utils module

General catchall for functions that don't make sense as methods.

`kademlia.utils.bytes_to_bit_string(bites)`

`kademlia.utils.digest(string)`

async `kademlia.utils.gather_dict(dic)`

`kademlia.utils.shared_prefix(args)`

Find the shared prefix between the strings.

For instance:

`sharedPrefix(['blahblah', 'blahwhat'])`

returns 'blah'.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

k

- `kademlia`, [13](#)
- `kademlia.crawling`, [13](#)
- `kademlia.node`, [14](#)
- `kademlia.routing`, [15](#)
- `kademlia.storage`, [16](#)
- `kademlia.utils`, [17](#)

Symbols

`__getitem__()` (*kademlia.storage.ForgetfulStorage method*), 16
`__getitem__()` (*kademlia.storage.IStorage method*), 16
`__setitem__()` (*kademlia.storage.ForgetfulStorage method*), 16
`__setitem__()` (*kademlia.storage.IStorage method*), 16

A

`add_contact()` (*kademlia.routing.RoutingTable method*), 15
`add_node()` (*kademlia.routing.KBucket method*), 15

B

`bytes_to_bit_string()` (*in module kademlia.utils*), 17

C

`cull()` (*kademlia.storage.ForgetfulStorage method*), 16

D

`depth()` (*kademlia.routing.KBucket method*), 15
`digest()` (*in module kademlia.utils*), 17
`distance_to()` (*kademlia.node.Node method*), 14

F

`find()` (*kademlia.crawling.NodeSpiderCrawl method*), 13
`find()` (*kademlia.crawling.ValueSpiderCrawl method*), 14
`find_neighbors()` (*kademlia.routing.RoutingTable method*), 16
`flush()` (*kademlia.routing.RoutingTable method*), 16
`ForgetfulStorage` (*class in kademlia.storage*), 16

G

`gather_dict()` (*in module kademlia.utils*), 17
`get()` (*kademlia.storage.ForgetfulStorage method*), 16
`get()` (*kademlia.storage.IStorage method*), 16

`get_bucket_for()` (*kademlia.routing.RoutingTable method*), 16
`get_ids()` (*kademlia.node.NodeHeap method*), 15
`get_node()` (*kademlia.node.NodeHeap method*), 15
`get_node_list()` (*kademlia.crawling.RPCFindResponse method*), 13
`get_nodes()` (*kademlia.routing.KBucket method*), 15
`get_uncontacted()` (*kademlia.node.NodeHeap method*), 15
`get_value()` (*kademlia.crawling.RPCFindResponse method*), 13

H

`happened()` (*kademlia.crawling.RPCFindResponse method*), 13
`has_in_range()` (*kademlia.routing.KBucket method*), 15
`has_value()` (*kademlia.crawling.RPCFindResponse method*), 13
`have_contacted_all()` (*kademlia.node.NodeHeap method*), 15
`head()` (*kademlia.routing.KBucket method*), 15

I

`is_new_node()` (*kademlia.routing.KBucket method*), 15
`is_new_node()` (*kademlia.routing.RoutingTable method*), 16
`IStorage` (*class in kademlia.storage*), 16
`iter_older_than()` (*kademlia.storage.ForgetfulStorage method*), 16
`iter_older_than()` (*kademlia.storage.IStorage method*), 16

K

`kademlia`
 module, 13
`kademlia.crawling`
 module, 13
`kademlia.node`
 module, 14

kademlia.routing
 module, 15
kademlia.storage
 module, 16
kademlia.utils
 module, 17
KBucket (*class in kademlia.routing*), 15

L

lonely_buckets() (*kademlia.routing.RoutingTable method*), 16

M

mark_contacted() (*kademlia.node.NodeHeap method*), 15
module
 kademlia, 13
 kademlia.crawling, 13
 kademlia.node, 14
 kademlia.routing, 15
 kademlia.storage, 16
 kademlia.utils, 17

N

Node (*class in kademlia.node*), 14
NodeHeap (*class in kademlia.node*), 14
NodeSpiderCrawl (*class in kademlia.crawling*), 13

P

popleft() (*kademlia.node.NodeHeap method*), 15
push() (*kademlia.node.NodeHeap method*), 15

R

remove() (*kademlia.node.NodeHeap method*), 15
remove_contact() (*kademlia.routing.RoutingTable method*), 16
remove_node() (*kademlia.routing.KBucket method*), 15
RoutingTable (*class in kademlia.routing*), 15
RPCFindResponse (*class in kademlia.crawling*), 13

S

same_home_as() (*kademlia.node.Node method*), 14
shared_prefix() (*in module kademlia.utils*), 17
SpiderCrawl (*class in kademlia.crawling*), 14
split() (*kademlia.routing.KBucket method*), 15
split_bucket() (*kademlia.routing.RoutingTable method*), 16

T

TableTraverser (*class in kademlia.routing*), 16
touch_last_updated() (*kademlia.routing.KBucket method*), 15

V

ValueSpiderCrawl (*class in kademlia.crawling*), 14